

Printing date 07/14/2025 Reviewed on 07/14/2025

1 Identification

- · Product identifier
- · Trade name: PermashadeTM LC Veneer Cement (All Shades)
- · Article number:

SDS 255-001.07R01, 71102, 71103, 71104, 71105, 71113, 71114, 71116, 71125, 35100, 35112, 5227, 35101, 5229, 35102, 5230, 35103, 5228

- · Application of the substance / the mixture Professional Dental Light Cure Veneer Cement
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support@ultradent.com

(800) 552-5512

- · Information department: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA): +1 (800) 424-9300 (INTERNATIONAL): +(703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.



Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS07, GHS08
- · Signal word Danger
- · Health Hazard-determining components of labeling:

Triethylene Glycol Dimethacrylate

Ethyl-4-Dimethylamino Benzoate

· Hazard statements

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Reviewed on 07/14/2025 Printing date 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

P302+P352 If on skin: Wash with plenty of water.

(Contd. of page 1)

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 1

Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous (components:	
109-16-0	Triethylene Glycol Dimethacrylate	≥1-≤10%
10287-53-3	Ethyl-4-Dimethylamino Benzoate	≥0.1-<1%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

See product labelling.

Keep receptacle tightly sealed.

· Specific end use(s) Professional Dental Light Cure Veneer Cement

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 4)

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 3)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve protection: Goggles recommended during refilling.
- · Body protection: Protective work clothing

0 D1 1	1 1	1 1		7	, •
9 Physical	ana	c_{I}	nemicai	l properi	ues

71 mysteat and estentieut properti	
· Information on basic physical and ch · General Information · Appearance:	nemical properties
Form:	Viscous
Color:	Shade dependent
· Odor:	Acrylic
· Odor threshold:	Not determined.
· pH-value:	Not applicable (non-aqueous)
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined
· Flash point:	>150 °C
· Flammability:	Not applicable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C:	1.85-1.95 g/cm³
Relative density	Not determined

(Contd. on page 5)

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 4)

Vapor densityEvaporation rateNot determined.Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

109-16-0 Triethylene Glycol Dimethacrylate

Oral LD50 >5,000 mg/kg (rat)

LC50 Fish 16.4 mg/l (Fish) (Toxicity to fish)

Dermal LD50 > 2,000 mg/kg (mouse)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 5)

12 Ecological information

· Toxicity

· Aquatic toxicity:

109-16-0 Triethylene Glycol Dimethacrylate

EC50 >100 mg/kg (Algae)

Biodegradability 28 days (Aerobic) (Biodegradability testing)

Aqua toxicity 32 mg/l (daphnia) (No Observed Effect Concentration)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	Not Regulated	
Packing group		
DOT, IMDG, IATA	Not Regulated	
Environmental hazards:	Not Applicable.	
Special precautions for user	Not Applicable	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not Applicable.	

(Contd. on page 7)

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 6)

· UN "Model Regulation": Not Regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 35	5 (extremely	hazardous	substances):
--------------	--------------	-----------	------------	----

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

Trade Secret

· TSCA (Toxic Substances Control Act):

109-16-0	Triethylene Glycol Dimethacrylate	ACTIVE
10287-53-3	Ethyl-4-Dimethylamino Benzoate	<i>ACTIVE</i>

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 Ethyl Alcohol

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)

	`	,	• (•			
	Trade S	ecret									A4
64-17-5	Ethyl Al	cohol	l								A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · **Department issuing SDS:** Environmental, Health, and Safety
- · Contact: Customer Service
- · Date of preparation / last revision 07/14/2025 / -

(Contd. on page 8)

Printing date 07/14/2025 Reviewed on 07/14/2025

Trade name: PermashadeTM LC Veneer Cement (All Shades)

(Contd. of page 7)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Sensitization - Skin 1: Skin sensitisation - Category 1

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

* * Data compared to the previous version altered.

HC.