



Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

1 Identification

- **Product identifier**
- **Trade name:** Peak™- ZM
- **Article number:** SDS 355-001.10R01, 1006644, 15229, 2463
- **Application of the substance / the mixture** Professional dental bonding agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com
(800) 552-5512
- **Information department:** Customer Service
- **Emergency telephone number:**
CHEMTREC (NORTH AMERICA) : +1 (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 1B

H360 May damage fertility or the unborn child.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Danger

- **Health Hazard-determining components of labeling:**

2-Hydroxyethyl Methacrylate

MDP

Ethyl-4-Dimethylamino Benzoate

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 1)

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

64-17-5	Ethyl Alcohol	<100%
868-77-9	2-Hydroxyethyl Methacrylate	≥1-<10%
	MDP	≥1-<10%
10287-53-3	Ethyl-4-Dimethylamino Benzoate	>0.1-<1%

- **Additional information:**
The specific chemical identity of composition is being withheld as a trade secret. The specific chemical identity is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of paragraph §1910.1200.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Immediately remove any clothing soiled by the product.
- **After inhalation:**
Seek medical treatment in case of complaints.
Give oxygen or artificial respiration as needed.
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Launder clothing before reuse.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do NOT induce vomiting.
If vomiting does occur, have victim lean forward to prevent aspiration.
Rinse mouth with water.
Seek medical treatment.
Never give anything by mouth to an unconscious person.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
Symptoms vary with alcohol level of the blood. Mild alcohol intoxication occurs at blood levels between 0.05-0.15%. Approximately 25% of individuals show signs of intoxication at these levels. Above 0.15% the person is definitely under the influence of ethanol; 50-95% of individuals are clinically intoxicated at these levels. Severe poisoning occurs when the blood is ethanol level is 0.3- 0.5%. Above 0.5% the individual will be comatose and death can occur. The unabsorbed ethanol should be removed by gastric lavage after intubating the patient to prevent aspiration. Avoid the use of depressant drugs or the excessive administration of fluids.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Water fog
 - Alcohol resistant foam
 - Water spray
 - Carbon dioxide
 - Dry Chemical
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
 - Carbon monoxide (CO)
 - May produce a floating fire hazard.
 - Static ignition hazard can result from handling and use.
 - Vapors may travel to source of ignition and flash back.
 - Vapors may settle in low or confined spaces.

Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may only be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire.

- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
 - Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
 - Stop leak. Contain spill if possible and safe to do so.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Highly flammable liquid. Eliminate all sources of ignition. All equipment used when handling this product must be grounded. A vapor suppressing foam may be used to reduce vapors. Do not touch or walk through spilled material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Use clean non-sparking tools to collect absorbed material.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

See Section 13 for disposal information.

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
*Avoid contact with eyes, skin, and clothing.
 Do not inhale vapor or mist.
 Open and handle container with care.
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**
*Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
*Metal containers involved in the transfer of this material should be grounded and bonded.
 Store in a cool location.*
- **Information about storage in one common storage facility:** *Store away from flammable substances.*
- **Further information about storage conditions:**
*Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Consult local fire codes for additional storage information.
 See product labelling.
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.*
- **Specific end use(s)** *Professional Dental Bonding Agent*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see section 7.*
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
*The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.*

64-17-5 Ethyl Alcohol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
STEL	Short-term value: 1000 mg/m ³
TLV	Short-term value: 1000 ppm
	A3
TWA	Short-term value: 1900 mg/m ³

- **Additional information:** *The lists that were valid during the creation were used as basis.*

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 5)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Observe good industrial hygiene practices.

Ensure that washing facilities are available at the work place.

Electrical equipment should be grounded and confirm to applicable electrical code.

When using do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Maintain eye wash fountain and quick-drench facilities in work area.

Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU)

Face protection

Use chemical safety goggles and/or a full face shield where splashing is possible.



Tightly sealed goggles

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 6)

· **Body protection:**

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Alcohol-like
Odor threshold:	Not determined.

· **pH-value:** Not applicable (non-aqueous)· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined

· **Flash point:** 13 °C· **Flammability:** Highly flammable.· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure:** Not determined.

Density at 20 °C:	0.8 g/cm ³
Relative density	Not determined
Vapor density	Not determined.
Evaporation rate	Not determined.

· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** Stable· **Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Possibility of hazardous reactions** Vapors may form explosive mixture with air.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 7)

- **Conditions to avoid**
 - Direct sunlight
 - Extreme temperature
 - Flames
 - Sparks
 - Heat
- **Incompatible materials:**
 - Alkali metals
 - Strong Inorganic Acids
 - Peroxides
 - Oxidizing Agents
 - Ammonia
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64-17-5 Ethyl Alcohol

Oral	LD50	5,600 mg/kg (guinea pig) 3,400 mg/kg (mouse) 7,060 mg/kg (rat)
Inhalative	LC50 Fish LC50/4 h	>10,000 mg/l (Fish) 39 mg/l (mouse) 20,000 mg/l (rat)

868-77-9 2-Hydroxyethyl Methacrylate

Oral	LD50	3,275 mg/kg (mouse) >5,000 mg/kg (rat)
Dermal	LC50 Fish LD50 LC50(Daphnia magna)	>100 mg/l (Fish) >3,000 mg/kg (rabbit) 24.1 mg/l (daphnia)

- **Primary irritant effect:**
 - on the skin:** Irritant to skin and mucous membranes.
 - on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 8)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

64-17-5 Ethyl Alcohol

Algae Toxicity | 1,000 mg/l (Algae)

868-77-9 2-Hydroxyethyl Methacrylate

EC50 | 345 mg/kg (Algae)

· **Persistence and degradability** Biodegradation is expected.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** Bioaccumulation is unlikely.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Dispose of contents/container in accordance with international, federal, state, and local regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UNI987

· **UN proper shipping name**

· **DOT**

Alcohols, n.o.s. (Ethyl Alcohol)

· **IMDG, IATA**

ALCOHOLS, N.O.S. (Ethyl Alcohol)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

(Contd. on page 10)

Safety Data Sheet


acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 9)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	II
· DOT, IMDG, IATA	II
· Environmental hazards:	Not Applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not Applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (ETHYL ALCOHOL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

64-17-5	Ethyl Alcohol	ACTIVE
868-77-9	2-Hydroxyethyl Methacrylate	ACTIVE
10287-53-3	Ethyl-4-Dimethylamino Benzoate	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2025

Reviewed on 08/04/2025

Trade name: Peak™- ZM

(Contd. of page 10)

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 Ethyl Alcohol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)**

64-17-5 Ethyl Alcohol

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:**

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health, and Safety

· **Contact:** Customer Service

· **Date of preparation / last revision** 08/04/2025 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**