

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

1 Identification

- **Product identifier**
- **Trade name:** *Ultradent™ Porcelain Etch*
- **Article number:** *SDS 4-001.16, 10324*
- **Application of the substance / the mixture** *Professional Dental Acid Etching Solution*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com*
- **Information department:** *Customer Service*
- **Emergency telephone number:**
*CHEMTREC (NORTH AMERICA) : (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887*

2 Hazard(s) identification

- **Classification of the substance or mixture**

*GHS06 Skull and crossbones*

- Acute Tox. 3 H301 Toxic if swallowed.*
- Acute Tox. 2 H310 Fatal in contact with skin.*
- Acute Tox. 3 H331 Toxic if inhaled.*

*GHS05 Corrosion*

- Skin Corr. 1A H314 Causes severe skin burns and eye damage.*
- Eye Dam. 1 H318 Causes serious eye damage.*

- **Label elements**
- **GHS label elements** *Void*
- **Hazard pictograms** *GHS05, GHS06*
- **Signal word** *Danger*
- **Health Hazard-determining components of labeling:**
Hydrofluoric Acid
- **Hazard statements**
*Toxic if swallowed or if inhaled.
Fatal in contact with skin.
Causes severe skin burns and eye damage.*
- **Precautionary statements**
*P260 Do not breathe dusts or mists.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash thoroughly after handling.*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: **Ultradent™ Porcelain Etch**

(Contd. of page 1)

- P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P311 Call a poison center/doctor.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

7664-39-3	Hydrofluoric Acid	≥7-≤10%
	☠ Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; ☠ Skin Corr. 1A, H314	

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.
 Remove breathing apparatus only after contaminated clothing have been completely removed.
 In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.
 In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Rub in Ca-gluconate solution or Ca-gluconate gel immediately.
 Immediately remove all soiled and contaminated clothing.
 Seek immediate medical advice.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent™ Porcelain Etch

(Contd. of page 2)

- Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Do not induce vomiting; immediately call for medical help.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam, dry chemical, carbon dioxide
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Unsuitable material for receptacle: glass or ceramic.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
See product labelling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent™ Porcelain Etch

(Contd. of page 3)

Keep receptacle tightly sealed.

· **Specific end use(s)** Professional Dental Acid Etching Solution

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7664-39-3 Hydrofluoric Acid

PEL Long-term value: 1* mg/m³, 3 ppm
as F, *sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm
Ceiling limit value: 5* mg/m³, 6* ppm
*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm
Ceiling limit value: 1.64 mg/m³, 2 ppm
as F; Skin; BEI

· **Ingredients with biological limit values:**

7664-39-3 Hydrofluoric Acid

BEI 3 mg/g creatinine
Medium: urine
Time: prior to shift
Parameter: Flourides (background)

10 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Flourides (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent™ Porcelain Etch

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Gel
Color:	Yellow
Odor:	Acidic
Odor threshold:	Not determined.

· **pH-value:** < 1.0

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C

· **Flash point:** Not applicable

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure:** Not determined.

Density at 20 °C:	1.1-1.2 g/cm ³
Relative density	Not determined
Vapor density	Not determined.
Evaporation rate	Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: **Ultradent™ Porcelain Etch**

(Contd. of page 5)

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined

· **Solvent content:**

Water: <90 %

VOC content: 0.00 %

0.0 g/l / 0.00 lb/gal

VOC (EC) 0.00 %

Solids content: <21.0 %

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions**

Reacts with organic substances.

Reacts with strong alkali.

Reacts with acids.

Reacts with certain metals.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:**

Hydrogen fluoride

Hydrogen

Corrosive gases/vapors

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	51.4-58.2 mg/kg
Dermal	LD50	51.4-58.2 mg/kg
Inhalative	LC50/4 h	5.14-5.82 mg/l

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent™ Porcelain Etch

(Contd. of page 6)

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Germ cell mutagenicity** Does not meet the classification criteria for this hazard class.

· **Carcinogenicity** Does not meet the classification criteria for this hazard class.

· **Reproductive toxicity** Does not meet the classification criteria for this hazard class.

· **Specific target organ toxicity - single exposure** Does not meet the classification criteria for this hazard class.

· **Specific target organ toxicity - repeated exposure** Does not meet the classification criteria for this hazard class.

· **Aspiration hazard** Does not meet the classification criteria for this hazard class.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UNI790

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: **Ultradent™ Porcelain Etch**

(Contd. of page 7)

· **UN proper shipping name**
 · **DOT**
 · **IMDG, IATA**

Hydrofluoric acid mixture
HYDROFLUORIC ACID mixture

· **Transport hazard class(es)**
 · **DOT**



· **Class**
 · **Label**

8 Corrosive substances
8, 6.1

· **IMDG**



· **Class**
 · **Label**

8 Corrosive substances
8/6.1

· **IATA**



· **Class**
 · **Label**

8 Corrosive substances
8 (6.1)

· **Packing group**
 · **DOT, IMDG, IATA**

II

· **Environmental hazards:** *Not Applicable.*

· **Special precautions for user**
 · **Hazard identification number (Kemler code):**
 · **EMS Number:**
 · **Segregation groups**
 · **Stowage Category**
 · **Stowage Code**
 · **Handling Code**

Warning: Corrosive substances
86
F-A,S-B
Strong acids
D
SW1 Protected from sources of heat.
SW2 Clear of living quarters.
H2 Keep as cool as reasonably practicable

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not Applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations**

On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L

· **IMDG**
 · **Limited quantities (LQ)**

1L

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: **Ultradent™ Porcelain Etch**

(Contd. of page 8)

· **Exempted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1790 HYDROFLUORIC ACID MIXTURE, 8 (6.1), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:**

Device is a strong acid and is extremely toxic. It is to be used only as directed with PPE, and only by licensed dental professionals.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health, and Safety· **Contact:** Customer Service· **Date of preparation / last revision** 09/23/2021 / -

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent™ Porcelain Etch

(Contd. of page 9)

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US