

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Identificat	ion
Product iden	tifier
Trade name	Ultradent TM Porcelain Etch
Article num	ber: SDS 4-001.16, 10324
Application	of the substance / the mixture Professional Dental Acid Etching Solution
	e supplier of the safety data sheet
Manufactur	
Ultradent Pr	oducts Inc. dent Drive (10200 S)
	n, UT 84095-3942
USA USA	, 01 04075 5742
	upport@ultradent.com
Information	department: Customer Service
	elephone number:
	C (NORTH AMERICA) :(800) 424-9300
	(INTERNATIONAL) : +(703) 527-3887
Hazard(s)	identification
11112.010(5)	achigication and a second s
Classificatio	n of the substance or mixture
\wedge	
G See G	HS06 Skull and crossbones
\sim	
Acute Tox. 3	H301 Toxic if swallowed.
Acute Tox. 2	H310 Fatal in contact with skin.
Acute Tox. 3	H331 Toxic if inhaled.
PT	
🛎 🀑 G	HS05 Corrosion
	4 H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Label eleme	nts
	lements Void
	grams GHS05, GHS06
Signal word	Danger
	rd-determining components of labeling:
Hydrofluoric	
Hazard state	
	lowed or if inhaled.
	act with skin.
	re skin burns and eye damage.
Precautional P260	ry statements Do not breathe dusts or mists.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash thoroughly after handling.
	(Contd. on pag

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

	(Contd. of page 1)
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P301+P330+P3	31 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P3	253 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/
	shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a poison center/doctor.
P305+P351+P3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification su	0

Classification system: · NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH 3	Health = 3
FIRE 0	Fire = 0
REACTIVITY 0	Reactivity $= 0$

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

7664-39-3 Hydrofluoric Acid

🛞 Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; 🔶 Skin Corr. 1A, H314

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation: Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Rub in Ca-gluconate solution or Ca-gluconate gel immediately. Immediately remove all soiled and contaminated clothing. Seek immediate medical advice.

(Contd. on page 3)

*≥*7-*≤*10%

US

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

(Contd. of page 2)

Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

• Information for doctor:

• *Most important symptoms and effects, both acute and delayed* No further relevant information available. • *Indication of any immediate medical attention and special treatment needed*

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Foam, dry chemical, carbon dioxide Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*

• Environmental precautions: No special measures required.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: glass or ceramic.
- · Information about storage in one common storage facility: Not required.
- *Further information about storage conditions:* See product labelling.

(Contd. on page 4)

US

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

Keep receptacle tightly sealed.

· Specific end use(s) Professional Dental Acid Etching Solution

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

7664-39-3 Hydrofluoric Acid

- PEL Long-term value: 1* mg/m³, 3 ppm as F, *sulfuric acid
- REL Long-term value: 2.5 mg/m³, 3 ppm Ceiling limit value: 5* mg/m³, 6* ppm *15-min, as F
- *TLV* Long-term value: 0.41 mg/m³, 0.5 ppm Ceiling limit value: 1.64 mg/m³, 2 ppm as F; Skin; BEI

· Ingredients with biological limit values:

7664-39-3 Hydrofluoric Acid

BEI 3 mg/g creatinine Medium: urine Time: prior to shift Parameter: Flourides (background)

> 10 mg/g creatinine Medium: urine Time: end of shift Parameter: Flourides (background)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

(Contd. of page 3)

US

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: Ultradent[™] Porcelain Etch

(Contd. of page 4)

US

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material is based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties	
General Information		
Appearance:	C^{-1}	
Form:	Gel Yellow	
Color: Odor:	Acidic	
Odor: Odor threshold:	Actaic Not determined.	
Oaor inresnoia:	Noi uelerminea.	
pH-value:	< 1.0	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C	
Flash point:	Not applicable	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C:	1.1-1.2 g/cm ³	
Relative density	Not determined	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

		(Contd. of page
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined	
· Solvent content:		
Water:	<90 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
VOC (EC)	0.00%	
Solids content:	<21.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with organic substances. Reacts with strong alkali. Reacts with acids. Reacts with certain metals.
- *Conditions to avoid* No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:
- Hydrogen fluoride
- Hydrogen
- *Corrosive gases/vapors*

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:	
--	--

ATE (Acute Toxicity Estimate)			
Oral	LD50	51.4-58.2 mg/kg	
	LD50	51.4-58.2 mg/kg	
Inhalative	LC50/4 h	5.14-5.82 mg/l	

Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

- on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

(Contd. on page 7)

____US

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

Corrosive

Irritant Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Germ cell mutagenicity Does not meet the classification criteria for this hazard class.

• *Carcinogenicity* Does not meet the classification criteria for this hazard class.

• *Reproductive toxicity Does not meet the classification criteria for this hazard class.*

• Specific target organ toxicity - single exposure Does not meet the classification criteria for this hazard class.

• Specific target organ toxicity - repeated exposure Does not meet the classification criteria for this hazard class.

· Aspiration hazard Does not meet the classification criteria for this hazard class.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Disposal should be in accordance with applicable regional, national and local laws and regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, IMDG, IATA	UN1790	
		(Contd. on page

US

Safety Data Sheet acc. to OSHA HCS

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

	(Contd. of pag
UN proper shipping name	
	Hydrofluoric acid mixture HYDROFLUORIC ACID mixture
IMDG, IATA	HIDROFLOORIC ACID mixture
Transport hazard class(es)	
DOT	
CORROSIVE 8 6	
- Class	8 Corrosive substances
Label	8, 6.1
IMDG	
Class	8 Corrosive substances
Label	8/6.1
IATA	
	8 Convegine substances
Class Label	8 Corrosive substances 8 (6.1)
	8 (0.1)
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not Applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	86
EMS Number:	F-A,S-B
Segregation groups	Strong acids
Stowage Category	
Stowage Code	SW1 Protected from sources of heat.
Handline Cala	SW2 Clear of living quarters.
Handling Code	H2 Keep as cool as reasonably practicable
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not Applicable.
Transport/Additional information:	rr
DOT Quantity limitations	On passanger aircraft/rail: 11
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	1L
	(Contd. on pa

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

	(Contd. of page 8)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1790 HYDROFLUORIC ACID MIXTURE, 8 (6.1), II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· ACGIH Carcinogenicity (American Conference of Governmental Industrial Hygienists)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

Chemical safety assessment:

Device is a strong acid and is extremely toxic. It is to be used only as directed with PPE, and only by licensed dental professionals.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health, and Safety

· Contact: Customer Service

· Date of preparation / last revision 09/23/2021 / -

(Contd. on page 10)

US

Printing date 09/23/2021

Reviewed on 10/07/2020

Trade name: UltradentTM Porcelain Etch

	(Contd. of page 9)
· Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Acute Tox. 2: Acute toxicity – Category 2	
Acute Tox. 3: Acute toxicity – Category 3	
Acute Tox. 1: Acute toxicity – Category 1	
Skin Corr. 1A: Skin corrosion/irritation – Category 1A	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
	US